ABN 94 606 513 160
Corner Hidden Valley Road & Vigilant Lane, Berrimah
PO Box 2393, Palmerston NT 0831
(08) 89 474 999
seca@secaust.com.au

NORTHERN TERRITORY OF AUSTRALIA

STRUCTURAL ENGINEERING CERTIFICATE OF COMPLIANCE

SECA REFERENCE: 26026 WSTxxxBDX54

Date of Issue: 5 February 2026

WINAICO Australia Pty Ltd
3/393 George Street
SYDNEY NSW 2000
Attn: Blair Pester

Email: b.pester@winaico.com

Design Certification for the WINAICO Solar Panel Module, Model WST-xxxBDX54 - 1800 x 1134 x 35mm
The Recommended Ultimate Design Strength of the WINAICO Solar Panel Module can resist wind force at the Limit State Design Capacity for the following support conditions:

When supported at 800mm centres	**4.71 kPa**
When supported at 1200mm centres	**4.35 kPa**

SCOPE

Structural Engineering Consultants Australia (SECA) Pty Ltd were engaged by WINAICO Australia Pty Ltd to carry out and witness three individual mechanical load tests (simulated static, wind load strength test). The test procedure followed was similar to the method outlined in AS4040.2:1992, Static Strength Test Regime. The testing was performed on new panels supplied by the client.

TEST PROCEDURE

The solar panel module(s) were mounted front side up and were free to deflect, this was to imitate a real-world situation. The electrical continuity or the cells themselves were not monitored during or after the tests. The load was applied by an airbag to the back of the panel and the centre deflection was monitored at 1kPa intervals as the load was applied by slowly inflating an air bag. A calibrated digital manometer was used to measure and track the test pressures, while a calibrated digital deflection meter was used to measure the centre (vertical) deflection of the solar panel.

A total of two panels were tested supported at 800mm centres and two panels were tested supported at 1200mm centres, each test was carried out once and tested on 31st January 2026. The applied factor for variability in accordance with AS/NZS 1170.0 Table B1 when determining the allowable design capacity for 1 test unit is 1.46 and for 2 test units is 1.38.

ABN 94 606 513 160
Corner Hidden Valley Road & Vigilant Lane, Berrimah
PO Box 2393, Palmerston NT 0831
(08) 89 474 999
seca@secaust.com.au

Test Results

Test 1:

Model: WINAICO WST-475BDX54-B2, Serial Number: WWPK090212509029008367
The panel **1800 x 1134 x 35mm** was mounted to the test rig with support points at **800mm** centres apart on each side with a cantilever/ overhang of approximately **500mm** at each end (measured from centre of supports).

The solar panel was observed to be able to support an equivalent design test pressure of **7 kPa** with a centre vertical deflection of **88mm**.

Test 2:

Model: WINAICO WST-475BDX54-B2, Serial Number: WWPK090212509029008827
The panel **1800 x 1134 x 35mm** was mounted to the test rig with support points at **800mm** centres apart on each side with a cantilever/ overhang of approximately **500mm** at each end (measured from centre of supports).

The solar panel was observed to be able to support an equivalent design test pressure of **6.5 kPa** with a centre vertical deflection of **86mm**.

Test 3:

Model: WINAICO WST-475BDX54-B2, Serial Number: WWPK090212509029008457
The panel **1800 x 1134 x 35mm** was mounted to the test rig with support points at **1200mm** centres apart on each side with a cantilever/ overhang of approximately **300mm** at each end (measured from centre of supports).

The solar panel was observed to be able to support an equivalent design test pressure of **6 kPa** with a centre vertical deflection of **72.1mm**.

Test 4:

Model: WINAICO WST-475BDX54-B2, Serial Number: WWPK090212509029008477
The panel **1800 x 1134 x 35mm** was mounted to the test rig with support points at **1200mm** centres apart on each side with a cantilever/ overhang of approximately **300mm** at each end (measured from centre of supports).

The solar panel was observed to be able to support an equivalent design test pressure of **6 kPa** with a centre vertical deflection of **75mm**.

STRUCTURAL ENGINEERING CONSULTANTS AUSTRALIA PTY LTD
ABN 94 606 513 160
Corner Hidden Valley Road & Vigilant Lane, Berrimah
PO Box 2393, Palmerston NT 0831
(08) 89 474 999
seca@secaust.com.au

Table 1: Test Summary
Recommended Ultimate Design Strength, Limit Design Capacity

Test	Panel Manufacturer, Model & Size (mm)	Support Points (mm)	Maximum Applied Load (kPa)	Material Variability Factor AS/NZS 1170.0 Table B1 – kt	Recommended Ultimate Design Strength Limit State Design Capacity (kPa)
1	**WINAICO WST-475BDX54-B2** 1800 x 1134 x 35mm **Serial Number:** WWPK090212509029008367	800	7.0	1.38	4.71
2	**WINAICO WST-475BDX54-B2** 1800 x 1134 x 35mm **Serial Number:** WWPK090212509029008827	800	6.5		
3	**WINAICO WST-475BDX54-B2** 1800 x 1134 x 35mm **Serial Number:** WWPK090212509029008457	1200	6.0	1.38	4.35
4	**WINAICO WST-475BDX54-B2** 1800 x 1134 x 35mm **Serial Number:** WWPK090212509029008477	1200	6.0		

In accordance with AS/NZS 1170.0 Table B1, where no reliable data for the co-efficient of variation of structural characteristics (Vsc) are available, a value of 10.0% maybe adopted for roof assembly cyclic testing, as recommended in Clause 6.1 of *The Draft Guide to LHL Cyclic Testing (Version 1)*, dated 9 April 2009 and issued by the Cyclone Testing Station.

Mechanical Properties

No. of Cells	108 (6 strings x 18 cells)
Cell Type	N type monocrystalline bifacial
Glass Thickness	2.0mm front & back
Dimensions (L x W x Frame thickness)	1800 x 1134 x 35mm
Weight	25 kg
Frame	Anodised Aluminium

ABN 94 606 513 160
Corner Hidden Valley Road & Vigilant Lane, Berrimah
PO Box 2393, Palmerston NT 0831
(08) 89 474 999
seca@secaust.com.au

Summary

The Recommended Ultimate Design Strength of the WINAICO **WST-xxxBDX54*** - **1800 x 1134 x 35mm** Solar Panel Module, can resist vertical wind force at the Limit State Design Capacity for the following support conditions:

** xxx = wattage of panel*

When supported at 800mm centres	**4.71 kPa**
When supported at 1200mm centres	**4.35 kPa**

Limitations

This certificate of compliance has been prepared on behalf of and for the exclusive use of WINAICO Australia Pty Ltd and forms part of the A.I.P certificate of compliance. These design capacities are only applicable for the panel size, model and support spacing as used in these tests. We accept that the wattage of the panel may vary, however this certificate is no longer valid if the any of the applicable Mechanical Properties used in the manufacture of these solar panel modules or if the manufacturing processes or techniques is changed or altered in any way. It is the responsibility of the manufacturer to advise or confirm if they are altered in any way as new tests and certification will be required.

Please note: The panel fixing clamps, the support rail or their associated fixings, may limit the structural design for installation.

Ray Colley **Director** **Structural Engineering Consultants Australia Pty Ltd**			**Company NT Registration Number** 169894ES
I certify that reasonable care has been taken to ensure that the structural engineering aspects of the works as described above have been designed in accordance with the requirements of the Building Code of Australia and the Northern Territory Building Regulations			
Name **Wisnu Lim** Nominee for Structural Engineering Consultants Australia Pty Ltd	**Nominee/Individual NT Registration Number** 145651ES	**Signature**	**Date** 6 February 2026

STRUCTURAL ENGINEERING CONSULTANTS AUSTRALIA PTY LTD
ABN 94 606 513 160
Corner Hidden Valley Road & Vigilant Lane, Berrimah
PO Box 2393, Palmerston NT 0831
(08) 89 474 999
seca@secaust.com.au

Appendix A

Test Results

Test Pressure	Test 1 800mm C/C Supports	Test 2 800mm C/C Supports
Load Applied (kPa)	Recorded Deflection (mm)	Recorded Deflection (mm)
1	14.8	14.9
2	27.5	29.0
3	38.9	41.6
4	49.1	53.0
5	58.8	63.2
6	74.9	81.2
6.5	82.3	86.0
7	88.0	

Test Pressure	Test 3 1200mm C/C Supports	Test 4 1200mm C/C Supports
Load Applied (kPa)	Recorded Deflection (mm)	Recorded Deflection (mm)
1	13.1	13.6
2	23.5	23.6
3	34.2	34.4
4	44.6	44.8
5	58.7	56.5
6	72.1	75.0